



AVOID HAND / ARM VIBRATION INJURIES

- Exclusive short and fast In-line stroke absorbs reciprocal cutting action of blades
- Change blades in less than 10 seconds
- Small, powerful and light weight
- Cutting Depth Control System & nylon control head avoids scratching glass or painted panels
- CE rated
- Low noise levels
- Reliable, long tool life
- Low vibration levels (HAV)
- Test ratings to ISO 5349 & ISO 8662
- Fully adjustable speed, stroke & power

AIR TOOL TECHNICAL DATA	METRIC	IMPERIAL
FREE SPEED – (BEATS/STROKES PER MINUTE)	6,500	6,500
RECIPROCAL STROKE LENGTH	6mm	¼"
NOISE	77 – 79 dba	77 - 79 dba
AIR INLET		¼" NPT
MAX. AIR PRESSURE	6.2 Bar	90 PSI
AIR CONSUMPTION (FREE AIR DELIVERY)	60(min) - 140(max) Litres per minute	2(min) - 5(max) CFM
WEIGHT	1.15kg	2.53 lb
OVERALL LENGTH excluding air hose	260mm	10 ¼"

POWERING THE BTB TOOL IN WORKSHOP OR WITH MOBILE AIR SUPPLY

A small portable air compressor is all that's required to power the BTB tool. Plug into fixed electrical outlet or vehicle mounted inverter system. Alternatively, it can also be powered by small, portable and silent CO₂ air bottle



CO₂ Air Bottle

Small Air Compressor



See BTB's website for spare parts for the WK10HD air tool